

⑬



Europäisches Patentamt
European Patent Office
Office européen des brevets

⑪ Publication number:

**0 240 213
B1**

⑫

EUROPEAN PATENT SPECIFICATION

④⑤ Date of publication of the patent specification:
21.03.90

⑤① Int. Cl.*: **A61F 13/15**

②① Application number: **87302435.0**

②② Date of filing: **20.03.87**

⑤④ Disposable diaper having an improved side closure.

③① Priority: **21.03.86 US 842326**

④③ Date of publication of application:
07.10.87 Bulletin 87/41

④⑤ Publication of the grant of the patent:
21.03.90 Bulletin 90/12

②④ Designated Contracting States:
AT BE CH DE ES FR GR IT LI LU NL SE

⑤⑤ References cited:
US-A- 3 776 232
US-A- 3 860 003
US-A- 4 253 461
US-A- 4 388 075
US-A- 4 402 690

⑦③ Proprietor: **THE PROCTER & GAMBLE COMPANY, One
Procter & Gamble Plaza, Cincinnati Ohio 45202(US)**

⑦② Inventor: **Toussant, John William, 8169 Shadybrook
Drive, West Chester Ohio 45069(US)**
Inventor: **Hasse, Margaret Henderson, 1251 Garden
Circle, Wyoming Ohio 45215(US)**

⑦④ Representative: **Gibson, Tony Nicholas et al, Procter &
Gamble (NTC) Limited Whitley Road, Longbenton
Newcastle upon Tyne NE12 9TS(GB)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

BACKGROUND OF THE INVENTION

This invention relates to disposable diapers having elasticized leg openings, and more particularly to an improved side closure for such disposable diapers. Still more particularly, this invention relates to an improved side closure for disposable diapers having elasticized leg openings comprising an outer fastening means and an inner fastening means.

Disposable diapers are well known articles of manufacture which are worn by infants and incontinent persons. Disposable diapers are worn about the lower torso and are intended to absorb and contain urine and feces thereby preventing the urine and feces from soiling, wetting, or otherwise contaminating the articles (e.g., clothing, bedding, etc.) which come into contact with the diaper wearer.

In general, disposable diapers all have the same basic structure which comprises an absorbent core encased between a liquid permeable user contacting topsheet and a liquid impermeable backsheet. The prior art, of course, teaches numerous variations of and elements in addition to the basic topsheet, backsheet, and absorbent core arrangement. For example, an improvement in the performance of disposable diapers has been achieved by the addition of an elastic means along the portion of the disposable diaper which contacts the wearer's thigh thereby providing elasticized leg openings when the diaper is worn.

When using a disposable diaper having elasticized leg openings the diaper user fits the diaper on the wearer and fastens it about the wearer's waist thereby effecting a side closure. Fitting the diaper about the wearer usually requires the front and back waist portions of the diaper to overlap each other. As the diaper is worn the movements of the wearer and the forces induced by the elastic means at the leg openings tend to cause the overlapping front and back waist portions to shift position relative to each other. In other words, overlapping front and back waist portions are subjected to forces which tend to cause the front and back waist portions to assume a position relative to each other which is different from the position they assume when the diaper is initially fitted to the wearer. Unless such shifting is limited the fit and containment characteristics of the diaper are degraded as the diaper is worn.

A number of concepts have been proposed for fastening a disposable diaper about the waist of the wearer. For example, U. S. Patent 3,848,594, which issued to K. B. Buell on November 19, 1974, teaches a tape fastening system for effecting a side closure in disposable diapers which has an improved manufacturers joint (i.e., the attachment between the fastener tape and the diaper which is made by the manufacturer). U. S. Patent 3,359,980 which issued to C. L. Rosenblatt on December 26, 1967 and U. S. Patent 3,638,651 which issued to D. Torr on February 1, 1972 both teach diapers in which a side closure is effected by overlapping portions of the dia-

per. Additional side closures are described in U. S. Patent 3,776,232 which issued to C. H. Schaar on December 4, 1973 and U. S. Patent 4,122,552 which issued to F. Tedford on October 31, 1978. Both the Tedford and Schaar patents are directed to improving the side closure by affixing the front and back waist portions together over a relatively large area. The Schaar patent achieves this result by using two fastening mechanisms while the Tedford patent uses a single fastening system which covers a relatively large area.

None of the foregoing patents are specifically directed to disposable diapers having elasticized leg openings and the special problems of maintaining good fit characteristics associated with such diapers. U. S. Patent 4,253,461 which issued to D. L. Strickland et al. on March 3, 1981, is directed to a disposable diaper having elasticized leg openings and achieves an improved side closure by providing separate fastening means at the waist and at the thigh.

In disposable diapers having elasticized leg openings, a portion of the contractive force generated by the elastic means used at the leg openings of such diapers is directed into the waist portion of the diaper. These forces together with the movements of the diaper wearer tend to cause shifting of the front and back waist portions. Shifting, as used herein, is the movement of the front and back waist portions relative to each other from the position they assume when the diaper is initially applied. When such relative motion occurs the fit about the wearers legs and waist becomes looser and less effective in containing waste products.

It is therefore an object of the present invention to provide an improved side closure for disposable diaper having elasticized leg openings.

A further object of the present invention is to provide an improved side closure which maintains the fit of the diaper at the waist and at the elasticized leg openings during wearing.

An additional object of the invention is to provide a disposable diaper having elasticized leg openings which has improved urine and feces containment characteristics.

SUMMARY OF THE INVENTION

According to the present invention there is provided a disposable diaper comprising:

- a liquid permeable topsheet;
- a liquid impermeable backsheet, said backsheet being affixed to said topsheet;
- an absorbent means for absorbing liquids, said absorbent means being encased between said topsheet and said backsheet;
- longitudinal marginal portions adjacent both longitudinal sides of the disposable diaper;
- elastic members operatively associated with both of said longitudinal marginal portions;
- first and second waist portions at opposite ends of the disposable diaper, said waist portions having longitudinally extending edges, said second waist portion having first and second panels, said panels

comprising those portions of the second waist portion overlain by the first waist portion when the diaper is fastened about the waist of the wearer;

an outer fastening means for maintaining said first waist portion and said second waist portion in an overlapping configuration, at least a portion of said outer fastening means being adjacent to the respective longitudinal sides of the disposable diaper; wherein the diaper also comprises inner fastening means for resisting shear forces between said respective overlapping first and second waist portions, each said inner fastening means being positioned in the region of its respective panel and having its major dimension oriented parallel to the longitudinally extending edges of said waist portions.

The disposable diaper of the present invention is provided with an outer fastening means and with an inner fastening means, which means together prevent relative motion between the front and back waist portions.

When the elasticized disposable diaper is placed around the waist of the wearer the waist portions of the elasticized disposable diaper are made to overlap. The outer fastening means affixes the overlapping portions of the waist portions to each other and maintains them in contact with each other. The inner fastening means limits and preferably prevents shifting of the overlapping portions thereby maintaining a good fit about the leg and waist of the wearer. The resulting disposable diaper thereby exhibits improved urine and feces containment characteristics when compared to prior art diapers.

The outer fastening means prevents separation of the overlapping waist portions. Thus, the outer fastening means must resist the tensile and peel forces encountered when the diaper is worn. Adhesive tapes as are well known in the disposable diaper art are suitable for use as the outer fastening means.

The inner fastening means may take many forms. Any means whereby shifting of the overlapping portions of the waist is limited and preferably prevented is suitable as an inner fastening means. For example, the inner fastening means may be an area which is covered with an adhesive so that when the waist portions of the diaper are overlapped they adhere to each other. Alternatively, the inner fastening means may comprise an area on one of the waist portions which when brought into contact with the other overlapping waist portion becomes mechanically entangled therewith. Further, the inner fastening means may be of a type that is either passive (i.e., requiring no special action by the diaper user) or active (i.e., requiring the diaper user to take action to activate the inside fastening means).

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a partially cutaway perspective view of an elasticized disposable diaper incorporating the present invention.

Figure 2 is a partially cutaway perspective view showing the disposable diaper of Figure 1 in the configuration it would assume when placed on a wearer.

DESCRIPTION OF A PREFERRED EMBODIMENT

Referring now to the drawings, there is shown a preferred embodiment of the present invention as it would be used in a disposable diaper intended to be worn by an infant. As used herein, the term "disposable diaper" refers to a garment generally worn by infants or incontinent persons, which is drawn up between the legs and fastened about the waist of the wearer and further, which is intended to be discarded after a single use (i.e., it is not intended to be laundered or otherwise restored and re-used).

Figure 1 is a partially cut away perspective view of the disposable diaper 10 of the present invention prior to its being folded and placed on the diaper wearer by the diaper user. As can be seen in Figure 1, a preferred diaper 10 basically comprises a liquid permeable topsheet 12, an absorbent means 14, a liquid impermeable backsheet 16 and elastic member 18. While the topsheet 12, absorbent means 14, liquid impermeable backsheet 16, and elastic member 18 may be assembled in a variety of well known configurations, a preferred disposable diaper configuration is described generally in U. S. Patent 3,860,003.

Figures 1 and 2 show a preferred embodiment of the diaper 10 in which the topsheet 12 and the backsheet 16 are coextensive and have length and width dimensions generally larger than those of the absorbent means 14. The topsheet 12 is superposed on the backsheet 16 thereby forming a periphery 20 of diaper 10. The periphery 20 defines the outer periphery or, in other words, the outer extent of the diaper 10. The periphery 20 comprises first end 22, second end 24, first longitudinal side 26, and second longitudinal side 28.

The topsheet 12 may be affixed to the backsheet 16 in any suitable manner as is well known in the diaper manufacturing art. In a preferred embodiment a multiplicity of longitudinal adhesive bands 30 of hot-melt adhesive are applied along the full length of the backsheet 16 generally parallel to the longitudinal centerline 70 of the backsheet 16. The longitudinal adhesive bands 30 serve to affix the topsheet 12 to the backsheet 16 at those points where these three components come together. The extent and location of the points where the topsheet 12, backsheet 16, and longitudinal adhesive bands 30 come together will depend on the spacing between the longitudinal adhesive bands 30 and on the distance the topsheet 12 and the backsheet 16 extend beyond the absorbent means 14. The number of longitudinal adhesive bands 30 and the spacing therebetween should be sufficient to securely bond the topsheet 12 to the backsheet 16 in the area between the periphery 20 and the edge of the absorbent means 14.

A hot-melt adhesive suitable for use as longitudinal adhesive bands 30 is manufactured by Eastman Chemical Products Company, of Kingsport, Tennessee and marketed under the tradename Eastobond A-3. It will be noted that the above described manner of affixing the topsheet 12 to the backsheet 16 causes the topsheet 12 to be affixed to the backsheet 16 intermittently along the first and second ends, 22 and 24. The absorbent means 14 is thereby

encased between the topsheet 12 and the backsheet 16. Of course, many alternative methods affixing the topsheet 12 to the backsheet 16 may be used with satisfactory results. For example, the topsheet 12 may be affixed to the backsheet 16 indirectly rather than directly as shown in Figure 1. Thus, an intermediate member may be used to affix the topsheet 12 to the backsheet 16.

The diaper 10 has first and second waist port 42 and 44 extending, respectively, from the first end 22 and the second end 24 of the diaper periphery 20 toward the lateral centerline 31 of the diaper 10 a distance from about 1/5 to about 1/3 the length of the diaper. The waist portions 42 and 44 comprise those portions of the diaper 10 which, when worn, encircle the waist of the wearer. The crotch portion 46 is that portion of the diaper 10 between first and second waist portions 42 and 44, and comprises that portion of the diaper 10 which, when worn, is positioned between the legs of the wearer and covers the lower torso of the wearer. First and second waist portions 42 and 44 are formed with longitudinally extending edges 45, 47, respectively disposed parallel to longitudinal center line 70.

The absorbent means 14 may be any means which is generally compressible, conformable, non-irritating to the wearer's skin, and which is capable of absorbing and retaining liquids. A preferred absorbent means 14 has first and second opposed faces 32 and 34 respectively and comprises an absorbent layer 36 and first and second tissue layers 38 and 40, respectively. The first and second tissue layers 38 and 40 overlay the major surfaces of the absorbent layer 36 to form the first and second opposed faces 32 and 34 of the absorbent means 14.

The absorbent layer 36 is intended to absorb and contain liquid and may be manufactured in a wide variety of sizes and shapes (e.g., rectangular, hourglass, etc.) and from a wide variety of liquid absorbent materials commonly used in disposable diapers, such as comminuted wood pulp which is generally referred to as airlaid. Other liquid absorbing materials may also be used in the manufacture of the absorbent layer 36 such as a multiplicity of plies of creped cellulose wadding, absorbent gelling material, absorbent foams or sponges, or any equivalent material or combination of materials. The total absorbent capacity of the absorbent layer 36 should, however, be compatible with the design liquid loading in the intended use of the disposable diaper 10. Further, the size and absorbent capacity of the absorbent layer 36 may be varied to accommodate wearers ranging from infants through adults.

The preferred embodiment of diaper 10 illustrated in Figures 1 and 2 has an hourglass shaped absorbent layer 36, and is intended to be worn by infants ranging in weight from 12 to 26 pounds (5 kgs. to 12 kgs.) The absorbent layer 36 is, therefore, a batt of airlaid approximately 16 inches (41 cm) long when measured along the longitudinal centerline, approximately 12 inches (32 cm) across the first and second ends 22 and 24, and approximately 4 inches (10 cm) across the narrowest part of the crotch portion 46. The absorptive capacity of the airlaid used for the absorbent layer 36 is sufficient to absorb and re-

tain from 8 to 16 grams of water per gram of absorbent material. Accordingly, the airlaid used in the preferred embodiment shown in Figures 1 and 2 weighs from 30 to 56 grams and has a generally uniform caliper. It should be understood, however, that the size, shape, configuration, and total absorbent capacity of the absorbent layer 36 may be varied to accommodate wearers ranging from infants through adults. Therefore, the dimensions, shape, and configuration of the absorbent layer 36 may be varied (e.g. the absorbent layer 36 may have a varying caliper, or a hydrophilic gradient, or may contain absorbent gelling materials).

The first and second tissue layers, 38 and 40, are intended to improve the tensile strength of the absorbent core 14 and to reduce the tendency of the absorbent layer 36 to split, lump or ball when wetted. The first and second tissue layers, 38 and 40, also help to improve lateral wicking of liquids, thereby providing a more even distribution of liquid in the absorbent layer 36. While a number of materials and manufacturing techniques may be used to manufacture the first and second tissue layers, 38 and 40, satisfactory results have been obtained with sheets of tissue paper having a basis weight of approximately 10 pounds per 3000 square feet (16 gms per square meter) and having an air permeability of approximately 100 cubic feet per minute per square foot (30 cubic meters per minute per square meter) over a 0.5 inch (13 mm) water pressure drop. While the first and second tissue layers, 38 and 40, are preferably coterminous with the absorbent layer 36, they may have different dimensions, a different configuration, or they may be omitted entirely.

The absorbent means 14 is superimposed on the backsheet 16 and is preferably affixed thereto by any means as is well known in the diaper art. For example, the absorbent core 14 may be secured to the backsheet 16 by a uniform continuous layer of adhesive, a patterned layer of adhesive, or an array of lines of spots of adhesive. In the preferred embodiment illustrated in Figures 1 and 2 the longitudinal adhesive bands 30 are used to affix the absorbent core 14 to the backsheet 16.

The backsheet 16 is impermeable to liquids and prevents liquids absorbed by the absorbent means 14 from wetting the undergarments, clothing, bedding, and other objects which contact the wearer of the disposable diaper 10. Preferably the backsheet 16 is a polyethylene film of from 0.0005 to 0.002 inches (0.012 to 0.051 mm) thick, although other flexible liquid impermeable materials may also be used. As used herein, the term "flexible" refers to materials which are compliant and which readily conform to the shape and contours of the human body. A suitable polyethylene film is manufactured by Monsanto Chemical Company and marketed in the trade as Film No. 8020. The backsheet 16 is preferably embossed and/or matte finished to provide a more clothlike appearance. Further, the backsheet 16 may have passages which permit vapors to escape from the absorbent means 14 while still preventing liquid from passing through the backsheet 16.

In a preferred embodiment, the backsheet 16 has a modified hourglass shape extending beyond the

absorbent layer 36 a minimum distance of at least 0.5 inches (1.3 cm) around the entire diaper periphery 20. The marginal portion 48 is that portion of the diaper 10 between the diaper periphery 20 and the edge of the absorbent layer 36 and comprises longitudinal marginal portions 50 adjacent first and second longitudinal sides 26 and 28, respectively in the crotch portion 46.

The topsheet 12 is compliant, soft feeling, and non-irritating to the wearer's skin and prevents the wearer of the diaper 10 from contacting the absorbent core 14. Further, the topsheet 12 is liquid permeable permitting liquids to readily penetrate through its thickness. A suitable topsheet 12 may be manufactured from a wide range of materials, such as natural fibers (e.g., wood or cotton fibers, synthetic fibers (e.g., polyester, polyethylene, polypropylene), or a combination thereof. Alternatively, the topsheet 12 may be a foam, such as the reticulated foams which are well known in the art or any of the formed films which are also well known in the art.

A number of manufacturing techniques can be used to manufacture the topsheet 12. For example, the topsheet 12 may be woven, nonwoven, spunbonded, carded, or the like. A preferred topsheet 12 is carded, and thermally bonded by means well known to those skilled in the nonwoven fabrics art.

Preferably the topsheet 12 has a weight of from 15 to 21 g/m² a minimum dry tensile strength of at least 400 grams per centimeter in the machine direction and a wet tensile strength of at least 55 grams per centimeter in the cross machine direction.

The elastic members 18 are affixed to the diaper 10 along both longitudinal marginal portions 50 so that they tend to draw and hold the diaper 10 against the legs of the wearer. Thus, when worn the diaper 10 will have elasticized leg openings. While this result may be accomplished by any of several means as are well known in the diaper art, a particularly preferred diaper construction incorporating elastic strips is described in detail in the hereinbefore referenced U. S. Patent 3 860 003, and a method and apparatus suitable for manufacturing a disposable diaper having elastic leg bands are described in U. S. Patent 4 081 301.

Relating the teachings of U. S. Patent 3 860 003 to the preferred embodiment shown in Figures 1 and 2 it can be seen that elastic members 18 are operatively associated with both longitudinal marginal portions 50 in the crotch portion 46 in an elastically contractible condition so that in a normally unrestrained configuration the elastic members 18 effectively contract or gather the longitudinal marginal portions 50.

As used herein the term "operatively associated with" refers to two or more components which act together. In the preferred embodiment shown in Figures 1 and 2 the elastic members 18 are operatively associated with both longitudinal marginal portions 50 in the crotch portion 46. Thus, the elastic members 18 are affixed to the longitudinal marginal portions 50 so as to cause the longitudinal marginal portions 50 in the crotch portion 46 to be contracted or gathered. A suitable method for incorporating elas-

tic members 18 into a disposable diaper is described in the aforesaid U. S. Patent 4,081,301.

In the preferred embodiment illustrated the elastic members 18 are affixed to a portion of the backsheet 16 in the longitudinal marginal portions 50. A suitable adhesive will be flexible and of sufficient adhesiveness to hold the elastic member 18 to the backsheet 16 while the elastic member 18 is stretched. An adhesive which has been used with satisfactory results is manufactured by Findley Adhesives Corporation of Elm Grove, Wisconsin and is marketed under the tradename Findley 581-334-01.

The elastic members 18 can be operatively associated with the longitudinal marginal portions 50 in an elastically contractible condition in at least two ways. For example, the elastic member 18 may be stretched and while in the stretched condition affixed to the uncontracted and unstretched longitudinal marginal portions 50. Alternatively, the longitudinal marginal portions 50 may be contracted (e.g., by pleating) and then affixing the unstretched elastic member 18 to the contracted longitudinal marginal portions 50.

Suitable elastic members 18 may be manufactured from a wide variety of elastic materials such as natural rubber, or elastomeric films such as Kraton, ethylene propylene-dimonomer, and polyurethane.

In addition, the elastic member 18 may take a multitude of configurations. For example, the width of the elastic members 18 may be varied from 0.015 inches to 1.0 inches (0.38 mm - 25 mm) or more; the elastic members 18 may comprise a single strip of elastic material or may comprise several parallel or non parallel strips of elastic material; or the elastic members 18 may be rectilinear or curvilinear. Still further, the elastic member 18 may be affixed to the diaper 10 in any of several ways which are well known in the art. For example, the elastic members 18 may be ultrasonically bonded or heat sealed into the diaper using a variety of bonding patterns or the elastic members 18 may simply be glued to the diaper 10. The outer fastening means with inner fastening means are particularly useful for preventing gapping at the elasticized leg openings caused by curvilinear elastic members.

One material which has been found to work well as an elastic member 18 is an elastic tape having a cross section of 0.007 inches by 0.25 inches (0.18 mm by 6.4 mm) and which is manufactured from natural rubber. Such a product is marketed by Easthampton Rubber Thread Company under the tradename L-1900 rubber compound. The preferred elastic member 18 produces a tensile force of 100 grams when stretched 100 percent from its relaxed condition.

The diaper 10 is provided with an outer fastening means 54 for maintaining the first and second waist portions 42 and 44 in an overlapping configuration when the diaper 10 is worn. Thus, the diaper 10 is fitted to the wearer and a side closure formed.

More specifically, the outer fastening means 54 affixes the first waist portion 42 to the second waist portion 44 thereby maintaining the first and second waist portions 42 and 44 in an overlapping configura-

ration. Thus, the outer fastening means 54 must be affixed to both the first waist portion 42 and to the second waist portion 44 in a manner and with a strength that is sufficient to resist the forces acting to cause the first and second waist portions 42 and 44 to separate during wearing.

The outer fastening means 54 may comprise any of the well known means for achieving a side closure such as Velcro strips or patches, buttons, or snaps. A preferred outer fastening means 54 is an adhesive tape 55 as is well known in the diaper art.

Any of the well known configurations and constructions may be used as the adhesive tape 55. For example, the adhesive tape 55 may be a single use tape or a multiple use tape (i.e., refastenable). A preferred adhesive tape 55 is a Y-shaped tape as described in detail in the previously mentioned US Patent 3848594.

The outer fastening means 54 are provided at both the first and second longitudinal sides, 26 and 28 respectively.

The preferred adhesive tape 55 illustrated in Figure 2 has a manufacturers end 56 and a users end 58. The manufacturers end 56 is that end of the adhesive tape 55 which the manufacturer of the diaper 10 affixes to the diaper 10 while the users end 58 is that end of the adhesive tape 55 which the user affixes to the diaper 10 when fitting the diaper 10 to the wearer. The manufacturers end 56 is affixed to the first waist portion 42 and after fitting the diaper 10 about the waist of the wearer the users end 58 is affixed to the second waist portion 44 thereby causing the diaper 10 to encircle the waist of the wearer and effecting a side closure.

The second waist portion 44 has panels 62. The panels 62 are those portions of the second waist portion 44 which are overlain by the first waist portion 42 when the diaper 10 is fastened about the waist of the wearer. The extent to which the second waist portion 44 is overlain and thus the extent to which panels 62 are formed will depend on the overall dimensions and shape of the diaper 10 and the size of the wearer.

The diaper 10 is provided with an inner fastening means 60 (Figure 2) for reducing and preferably preventing shifting of the panels 62 and the first waist portion 42 relative to each other. The inner fastening means 60, therefore, resists the shear forces which act to cause the panels 62 to shift their position relative to the first waist portion 42 as the diaper 10 is worn.

As described hereinabove, the diaper 10 is generally fitted, to the wearer so that the diaper 10 conforms to the wearers waist and legs thereby providing protection against leakage. It is desirable to maintain the diaper 10 in the configuration in which it is applied so that the conformity about the wearers waist and legs is also maintained. Thus, it is important that the panels 62 be retarded and preferably prevented from shifting their position relative to the first waist portion 42 while the diaper 10 is worn. The purpose of the inner fastening means 60, therefore is to maintain the panels 62 and the first waist portion 42 in the position relative to each other that

they assume when the diaper 10 is initially fitted to the wearer. As shown in Figure 2, inner fastening means 60 is disposed with its major dimension oriented parallel to the longitudinally extending edges 45 and 47 of the waist portions 42 and 44.

After the initial placement of the panels 62 against the first waist portion 42 during fitting of the diaper 10 to the wearer the panels 62 -- first waist portion 42 interface is subjected to shear forces which act in such a manner as to cause the panels 62 and first waist portion 42 to shift position relative to each other. If such a shift in position of the panels 62 and first waist portion 42 occurs the conformity of the diaper 10 about the waist and legs of the wearer will be degraded. Thus, the inner fastening means 60 must have a shear resistance sufficient to resist the shear forces acting on the panels 62 -- first waist portion 42 interface. These shear forces are induced by the elastic members 18 and by the movements of the diaper wearer.

As used herein the term "shear forces" refers to the forces encountered during the wearing of the diaper 10 and which forces tend to cause the panels 62 to shift position with respect to the first waist portion 42. Shear forces are to be distinguished from peel forces which cause the panels 62 to separate or move away from the first waist portion 42. Peel forces are resisted by the outer fastening means 54 while the shear forces are resisted by the inner fastening means 60.

While the inner fastening means 60 may take many alternative configurations it has been found that an inner fastening means 60 capable of resisting shear forces of at least 500 grams and preferably at least 750 grams and most preferably at least 1000 grams works well. The shear resistance of the inner fastening means 60 may readily be determined in accordance with the procedure described herein-after.

The inner fastening means 60 may either be integral (i.e., a discrete separate element affixed to diaper 10) or unitary (i.e., a single piece of material that is neither divided nor discontinuous) with the panels 62, or with the first waist portion 42, or with both the panels 62 and the first waist portion 42. For example, the surface of the panels 62 which contacts the first waist portion 42 may be manufactured so as to mechanically engage that portion of the first waist portion 42 which overlays the panel 62. Alternatively the inner fastening means 60 may comprise a layer of adhesive applied to the panels 62 which adhesive has a high enough shear resistance to prevent the panels 62 from shifting with respect to the overlapping portions of the first waist portions 42. Alternatively, the adhesive may be applied to the first waist portion 42. It is not necessary for the inner fastening means 60 to have a high resistance to peel since the overlapping portions of the first and second waist portion 42 and 44, are maintained against each other by the outer fastening means 54.

In the preferred embodiment illustrated the inner fastening means 60 is integral with the panels 62 comprising a layer of material affixed to the panels 62 and capable of mechanically engaging the top-sheet 12 (i.e., the layer of material becomes entan-

gled in the fibers of the topsheet 12). A suitable material is marketed by 3M Corporation, St. Paul, Minnesota, under the tradename SJ 3492. An alternatively preferred inner fastening means 60 comprises a layer of adhesive such as that marketed by 3M of St. Paul, Minnesota under the tradename OEM 1524 which is applied to the panels 62.

The inner fastening means 60 is preferably affixed to both panels 62 and covers an area 25.5 mm wide (i.e., generally perpendicular to longitudinal centerline 20) by 255 mm long (i.e., generally parallel to longitudinal centerline 70) at the corners of the diaper 10.

The shear resistance of the inner fastening means 60 is a measure of the ability of the inner fastening means 60 to resist shear forces and thus prevent the panels 62 from shifting position with respect to the first waist portion 42. The shear resistance of the inner fastening means 60 may be determined using any method which measures the force required to first initiate movement between the panels 62 and the first waist portion 42 at a contact pressure of 17 grams/square centimeter. The following procedure for determining the shear resistance of the inner fastening means 60 was used with good results. Two samples are cut from the diaper 10. The first sample is cut from one of the panels 62 and comprises that portion of the panel 62 which is overlapped by the first waist portion 42 when the diaper 10 is worn and the second sample is cut from the first waist portion 42 and comprises that portion of the first waist portion 42 which overlaps the panel 62 when the diaper is worn. The first sample should have dimensions sufficient to permit it to cover the face of a 63.5 millimeters square sled and the second sample should be at least 63.5 millimeters square. If the inside fastening means 60 has dimensions less than 63.5 millimeters by 63.5 millimeters the samples should be selected so as to encompass as much of the inside fastening means 60 as possible.

Both samples are stripped of any loose or extraneous material such as the absorbent means 14. The first sample is affixed to a friction sled which is 63.5 millimeters square by 6.0 millimeters thick and which is covered on at least one surface with a 3.2 millimeters thick, medium-density foam rubber which is wrapped snugly around the sled and fastened in position. The wrapped sled and additional weights weigh 710 ± 5 grams. In affixing the first sample to the friction sled the inner surface of the backsheet 16 of the first sample is placed against the friction sled. The second sample is affixed to a friction platform with the inner surface of the topsheet 12 of the second sample against the friction platform.

The covered friction sled is then set on the second sample thus simulating the conditions when the diaper 10 is worn. A shear force is applied to the friction sled, along a line parallel to the friction platform and the force required to first initiate a sliding of the friction sled relative to the friction platform is the shear resistance of the inner fastening means 60. The shear force may be applied and measured using any technique or apparatus that will be known to those skilled in the testing art. It has been found,

however, that the shear resistance of the inside fastening means may easily be determined using a tensile tester of the types manufactured by Instron Corporation of Canton, Massachusetts and marketed under the tradename Instron 1101-TM, 1102-TMS, 1122 and 1130.

Claims

1. A disposable diaper comprising: a liquid permeable topsheet (12);
a liquid impermeable backsheet (16), said backsheet being affixed to said topsheet;
an absorbent means (14) for absorbing liquids, said absorbent means being encased between said topsheet (12) and said backsheet (16);
longitudinal marginal portions (50) adjacent both longitudinal sides (26, 28) of the disposable diaper;
elastic members (18) operatively associated with both of said longitudinal marginal portions;
first and second waist portions (42, 44) at opposite ends (22, 24) of the disposable diaper, said waist portions having longitudinally extending edges (45, 47), said second waist portion (44) having first and second panels (62), said panels comprising those portions of the second waist portion (44) overlain by the first waist portion (42) when the diaper is fastened about the waist of the wearer; an outer fastening means (54) for maintaining said first waist portion (42) and said second waist portion in an overlapping configuration, at least a portion of said outer fastening means (50) being adjacent to the respective longitudinal sides (26, 28) of the disposable diaper; characterised in that the diaper also comprises inner fastening means (60) for resisting shear forces between said respective overlapping first and second waist portions (42, 44), each said inner fastening means (60) being positioned in the region of its respective panel (62) and having its major dimension oriented parallel to the longitudinally extending edges (45, 47) of said waist portions (42, 44).
2. A disposable diaper according to claim 1 wherein said inner fastening means has a shear resistance of at least 500 grams.
3. A disposable diaper according to either one of claims 1 and 2 wherein the shear resistance of said inner means is at least 750 grams.
4. A disposable diaper according to any one of claims 1-3 wherein the shear resistance of said inner means is 1000 grams.
5. A disposable diaper according to any one of claims 1-4 wherein said inner fastening means comprises a layer of adhesive applied to said first panel and to said second panel.
6. A disposable diaper according to any one of claims 1-4 wherein said inner fastening means comprises a layer of adhesive applied to said first waist portion.
7. A disposable diaper according to any one of claims 1-4 wherein said inner fastening means comprises segments of said first panel and said second panel having a surface texture which engages said first waist portion.

8. A disposable diaper according to any one of the preceding claims wherein said elastic members are curvilinear.

9. A disposable diaper according to any one of claims 1-7 wherein said elastic members are rectilinear.

Revendications

1. Une couche à jeter après usage comprenant: une feuille de dessus (12) perméable aux liquides; une feuille de fond (16), imperméable aux liquides, ladite feuille de fond étant fixée à ladite feuille de dessus;

un moyen absorbant (14) pour absorber les liquides ledit moyen absorbant étant enfermé entre ladite feuille de dessus (12) et ladite feuille de fond (16); des parties marginales longitudinales (50) près des deux côtés longitudinaux (26, 28) de la couche à jeter après usage;

des éléments élastiques (18) associés de manière active avec deux desdites parties marginales longitudinales;

des première et seconde parties de taille (42, 44), aux extrémités opposées (22, 24) de la couche à jeter après usage, lesdites parties de taille ayant des bords s'étendant longitudinalement (45, 47), ladite seconde partie de taille (44) ayant un premier et un second panneaux (62), lesdits panneaux comportant ces parties de la seconde partie de taille (44) recouverte par la première partie de taille (42) lorsque la couche est attachée autour de la taille de l'utilisateur;

un moyen d'attache extérieur (54) pour maintenir ladite première partie de taille (42) et ladite seconde partie de taille selon une configuration à recouvrement, au moins une partie dudit moyen d'attache extérieur (50) étant adjacent aux bords longitudinaux respectifs (26, 28) de la couche à jeter après usage; caractérisé en ce que la couche comporte en outre un moyen d'attache intérieur (60) pour résister aux forces de cisaillement entre lesdites première et seconde parties de taille respectives en recouvrement (42, 44), chacun dudit moyen d'attache intérieur (60) étant disposé dans la zone de son panneau respectif (62) et ayant sa plus grande dimension orientée parallèlement aux bords s'étendant longitudinalement (45, 47) desdites parties de taille (42, 44).

2. Une couche à jeter après usage selon la revendication 1, dans laquelle ledit moyen d'attache intérieur a une résistance aux forces de cisaillement d'au moins cinq cents grammes.

3. Une couche à jeter après usage selon l'une ou l'autre des revendications 1 et 2, dans laquelle la résistance au cisaillement dudit moyen intérieur est au moins de sept cent cinquante grammes.

4. Une couche à jeter après usage selon l'une quelconque des revendications 1-3, dans laquelle la résistance au cisaillement dudit moyen intérieur est de mille grammes.

5. Une couche à jeter après usage selon l'une quelconque des revendications 1-4, dans laquelle ledit moyen d'attache intérieur comporte une couche

d'adhésif appliquée audit premier panneau et audit second panneau.

6. Une couche à jeter après usage selon l'une quelconque des revendications 1-4 dans laquelle ledit moyen d'attache intérieur comporte une couche d'adhésif appliquée à ladite première partie de taille.

7. Une couche à jeter après usage selon l'une quelconque des revendications 1-4 dans laquelle ledit moyen d'attache intérieur comporte des segments dudit premier panneau et dudit second panneau ayant une texture de surface qui vient en contact avec ladite première partie de taille.

8. Une couche à jeter après usage selon l'une quelconque des revendications précédentes, dans laquelle lesdits éléments élastiques sont curvilignes.

9. Une couche à jeter après usage selon l'une quelconque des revendications 1-7, dans laquelle lesdits éléments élastiques sont rectilignes.

Patentansprüche

1. Wegwerfwindel mit: einer flüssigkeitsdurchlässigen Oberlage (12);

einer flüssigkeitsundurchlässigen Unterlage (16), die an der Oberlage befestigt ist;

einem Absorbiermittel (14) zum Absorbieren von Flüssigkeiten, wobei das Absorbiermittel zwischen der Oberlage (12) und der Unterlage (16) eingeschlossen ist;

Längsrandteile (50) nahe beiden Längsseiten (26, 28) der Wegwerfwindel;

elastischen Elementen (18), die mit beiden Längsrandteilen in Wirkverbindung stehen;

ersten und zweiten Hüftteilen (42, 44) an gegenüberliegenden Enden (22, 24) der Wegwerfwindel, wobei die Hüftteile in Längsrichtung verlaufende Ränder (45, 47) haben, wobei der zweite Hüftteil (44) erste und zweite Felder (62) aufweist, die jene Abschnitte des zweiten Hüftteiles (44) enthalten, die vom ersten Hüftteil (42) überlagert werden, wenn die Windel um die Hüfte des Trägers befestigt wird;

einer äußeren Befestigungseinrichtung (54), um den ersten Hüftteil (42) und den zweiten Hüftteil in überlappendem Zustand zu halten, wobei zumindest ein Teil der äußeren Befestigungseinrichtung (50) nahe den entsprechenden Längsseiten (26, 28) der Wegwerfwindel liegt; dadurch gekennzeichnet, daß die Windel auch innere Befestigungseinrichtungen (60) aufweist, um Scherkräften zwischen den einander überlappenden ersten und zweiten Hüftteilen (42, 44) zu widerstehen, wobei jede innere Befestigungseinrichtung (60) im Bereich ihres zugeordneten Feldes (62) angeordnet ist und ihre Hauptabmessung parallel zu den in der Längsrichtung verlaufenden Rändern (45, 47) der Hüftteile (42, 44) orientiert ist.

2. Wegwerfwindel nach Anspruch 1, bei welcher die innere Befestigungseinrichtung eine Scherfestigkeit von zumindest 500 g hat.

3. Wegwerfwindel nach Anspruch 1 oder 2, bei welcher die Scherfestigkeit der inneren Befestigungseinrichtung zumindest 750 g beträgt.

4. Wegwerfwindel nach einem der Ansprüche 1 bis 3, bei welcher die Scherfestigkeit der inneren Befestigungseinrichtung 1000 g beträgt.

5. Wegwerfwindel nach einem der Ansprüche 1 bis 4, bei welcher die innere Befestigungseinrichtung eine Schicht aus Klebstoff aufweist, die am ersten Feld und am zweiten Feld angebracht ist.

5

6. Wegwerfwindel nach einem der Ansprüche 1 bis 4, bei welcher die innere Befestigungseinrichtung eine Schicht aus Klebstoff aufweist, die am ersten Hüftteil angebracht ist.

10

7. Wegwerfwindel nach einem der Ansprüche 1 bis 4, bei welcher die innere Befestigungseinrichtung Segmente des ersten Feldes und des zweiten Feldes aufweist, die eine Oberflächentextur haben, welche am ersten Hüftteil angreift.

15

8. Wegwerfwindel nach einem der vorhergehenden Ansprüche, bei welcher die elastischen Elemente gekrümmt sind.

9. Wegwerfwindel nach einem der Ansprüche 1 bis 7, bei welcher die elastischen Elemente geradlinig sind.

20

25

30

35

40

45

50

55

60

65

Fig. 1




Fig. 2

